

Tire size LI/SSY	Rim Width	Section width (mm)	Overall diame- ter (mm)	Loaded static radius (mm)	Rolling circum- ference (mm)	Speed Radius Index	Tire load capacity (kg) at tire pressure (bar)						Speed (km/h)
							1,2	1,4	1,6	2,0	2,4	2,8	
<b>Advanced tire</b>													
<b>24 Inch</b>							<b>1,2</b>	<b>1,4</b>	<b>1,6</b>	<b>2,0</b>	<b>2,4</b>	<b>2,8</b>	
VF 500/85R24 CFO 167A8/167B Ⓟ	18	539*	1494*	618	4287	700	3485	3870	4250	4625	4875	5450	50
	16	519*					3485	3870	4250	4625	4875	5450	≤ 40
							3890	4320	4745	5200	5525	6015	30 cycl.
							4640	5150	5660	6200	6590	7170	15 cycl.
<b>26 Inch</b>							<b>1,2</b>	<b>1,4</b>	<b>1,6</b>	<b>2,0</b>	<b>2,4</b>	<b>2,8</b>	
VF 620/70R26 CFO 173A8/173B Ⓟ	23	667*	1563*	661	4528	725	4225	4685	5150	5600	6000	6500	50
	21	647*					4225	4685	5150	5600	6000	6500	≤ 40
	20	637*					4665	5175	5690	6340	6695	7280	30 cycl.
							5560	6170	6780	7555	7985	8680	15 cycl.
VF 750/65R26 CFO 177A8/177B Ⓟ	28	802*	1676*	705	4846	775	5165	5660	6150	6700	7300		50
	27	792*					5165	5660	6150	6700	7300		≤ 40
	25	772*					5790	6340	6890	7540	8190		30 cycl.
							6900	7560	8215	8990	9765		15 cycl.
<b>28 Inch</b>							<b>1,2</b>	<b>1,4</b>	<b>1,6</b>	<b>2,0</b>	<b>2,4</b>	<b>2,8</b>	
VF 600/65R28 CFO 163A8/163B Ⓟ	21	627*	1523*	656	4450	700	3675	4025	4375	4875			50
	20	617*					3675	4025	4375	4875			≤ 40
							4095	4485	4875	5525			30 cycl.
							4885	5350	5815	6590			15 cycl.
<b>30 Inch</b>							<b>1,2</b>	<b>1,4</b>	<b>1,6</b>	<b>2,0</b>	<b>2,4</b>	<b>2,8</b>	
VF 500/85R30 CFO 170A8/170B Ⓟ	18	539*	1646*	694	4765	775	3795	4210	4625	5000	5450	6000	50
	16	519*					3795	4210	4625	5000	5450	6000	≤ 40
							4265	4730	5200	5690	6015	6500	30 cycl.
							5085	5640	6200	6780	7170	7750	15 cycl.

\* ETRTO max. values

Ⓟ Planned

Specifications are subject to change without notice.

For further technical information, see data sheets.

For details regarding product availability, please contact your local sales representative.